

PAR-MOVE SERIES - STRONGER THAN EVER!!

NEW

SX119 PRO

PAR-MOVE CONCEPT HIGH PERFORMANCE SUPER-AUTOMATIC TYRE CHANGER WITH DUAL ASSIST ARM AND POWER X

YouTube *Watch the video*

SX119 PRO

www.giuliano-automotive.com



Suitable for **Tubeless** tyre bead seating system (optional).

Motoinverter

MOTOINVERTER
Faster, more accurate and reliable drive for your tyre changer.

Available in 3ph-2 speed, 1ph-2 speed (inverter) and 1ph - 1 speed version

5 YEAR WARRANTY

5 YEAR WARRANTY
on POWERX, PAR-MOVE and GEARBOX

✓ Robust fixed vertical tower with innovative **PAR-MOVE** parallelogram operating arm [**Giuliano Patent**].

✓ Vertical tower with built-in air tank.

SPACE SAVER: PAR-MOVE design [**Patented**] enables the tyre machine to be installed against the wall, requiring **no additional rear space**.

HP119 Additional auxiliary helper system (standard) provides a **valuable support** in mounting /demounting Run Flat, UHP and low profiled tyres.

✓ Fitting head designed for both standard and low profiled tyre applications.

POWERX grants **double** (uniform) clamping power on jaws, and an almost endless durability and reliability of your turntable!!! [Giuliano Patent].

Approved wdk

✓ Reinforced Chassis. Fixed vertical tower and parallelogram operating arm [**Patented**] makes SX119Pro extremely robust and stiff, granting increased rigidity and eliminating all flexes.

✓ Tabletop thickness 14 mm with **POWERX** four cylinders clamping system [**Giuliano Patent**].

Patented **PO SYSTEM** (standard) **automatically** moves the bead breaker shovel back to the starting position, after its penetration.



✓ Tools Storage Box (standard). Tyre inflation by pedal (standard).



✓ Adjustable BB shovel stroke. Super-quick and Simple.

✓ Double rotation speed by pedal.

✓ "Easy Access" extractable pedal box for quick service.

✓ Bead breaker double effect Cylinder Ø 200 mm.



Intensive use

220V-1ph Inverter

A very practical **Wheel Lifter** reduces effort and increases productivity (optional).

EXTENSIVE SELECTION OF OPTIONAL ACCESSORIES

STANDARD FEATURES

Rim clamping from outside	10" - 27"
Rim clamping from inside	12" - 29"
Max. tyre diameter	1100 mm (43")
Max. tyre width	415 mm (16")
Bead breaker cylinder force at 10 Bar	30800 N
Operating pressure	10 Bar (145 Psi)
Power supply	400V-3ph-2 speed 220V-1ph/220V-1ph-2 speed
Motor power	0,8 / 1,1 kW (3 ph)
Rotation speed	7 - 14 rpm
Pre-set tyre inflating pressure	3,5 bar (50 Psi)
Net weight	408 kg
Max. overall dimensions	1390x1350x2170 mm

STANDARD ACCESSORIES



• Bead lifting lever • Lube paste bucket and Brush • Plastic protectors for mounting/demounting tool • 2 Protectors for bead breaker shovel • Jaw protectors for alloy rims • Lubricator + Pressure regulator • Bucket support

GROUP GIULIANO S.p.A.

MADE IN ITALY